




ANCHOR HANDLING TUG SUPPLY VESSEL (73M)

ANCHOR HANDLING TUG SUPPLY VESSEL (73M)



Principal specifications

Length	73.7m
Breadth moulded	16m
Depth to main deck	7.2m
Design draft	5.4m
Deadweight at design draft	1,668t
Scantling draft	6m
Deadweight at scantling draft	2,316t

Dynamic Positioning (DP) System

DP2

Classification

LR✕100A1 Offshore Supply Vessel/ Anchor Handler, WDL (5.5t/m², main deck aft of Fr.68), RD (Liquid Mud/Brine Tanks, 2.5), LFPL (Methanol, 12°C, Methanol Tanks), HNLS, Fire-Fighting Ship 1 (2400m³/h) with water spray, ✕LMC, DP (AA)

Main machinery

Main engine	2 x MAK 9M32C 4,500kW at 600rpm
Auxiliary engine	3 x CAT 3412C 590kW at 1,800rpm
Bow thrusters	2 x KaMeWa CP Ulstein- 3000AGSC-KP-94XF5/47 1 x KaMeWa CP Ulstein Stern Thruster
Main crane	1 x TTS GPT 150-10-15, 10t (2 fall) at 8m outreach
Deck equipment	2 x Brattvaag Capstans, 2 Tugger Winches, 1 Windlass 1 x Towing/ Anchor handling winch of Waterfall type
Generators	4 x 590kW (diesel) 2 x 1,200kW (shaft)

Speed

Speed	14.3kts at 4.55m draft, 85% MCR
-------	---------------------------------

Tonnage

Gross tonnage	2,850t
Net tonnage	850t

Tank capacity

Potable water	473m ³
Drill water/ SWB	680m ³
Ship's fuel oil	580m ³
Cargo fuel oil	445m ³
Dirty oil	6.5m ³
Lub oil	25m ³
Foam & dispersant	10m ³ (each)
Methanol tank	140m ³
Bulk cement	3 x 72.91m ³ 1 x 50.97m ³
Mud tanks	500m ³
Bilge holding	13m ³

Navigation

2 ARPA Radars, 1 Echo Sounder, 1 ECDIS, 2 GPS, 3 Gyroscopes

Life-saving equipment

Life raft	4 x 25 pax 4 x 20 pax
Life buoy	8

Accommodation

Single cabins	4
Double cabins	17
Quad cabins	5

ST Engineering Marine Ltd.

Main yard: 7 Benoi Road, Singapore 629882
Tel: (65) 6861 2244 Fax: (65) 6861 3028
www.stengg.com

Tuas yard: 60 Tuas Road, Singapore 638501
Tel: (65) 6862 2902/3 Fax: (65) 6862 5382
E: mktg.marine@stengg.com